# DOUTHITT Heavy Duty Direct Method Screen Vacuum Frames

#### MODEL DMW

Space Saver Wall Model

Loads Glass down and then tilts up to Vertical position for Printing.

#### PRICE INCLUDES:

- (1) Special DOUTHITT "DEEP DRAW" BLACK Blanket. Under vacuum, this blanket swiftly molds itself to the shape of the silk screen frame and holds your positive in perfect contact.
- (2) Heavy Duty Vacuum Pump and Motor.
- (3) Vacuum Relief Bleeder Valve and vacuum gauge.
- (4) Counterbalanced sliding weights concealed in side tubes provide lifelong assistance in raising of blanket frame and tilting of glass and blanket frames.
- (5) Optic clear A-1 Select Glass.
- (6) Ten Foot Service Cord.

Size Inside	Crating	Ht. 72"	Approx.
Blanket		Width Left	Crated
Beading		To Right	Weight
35 x 45 38 x 50 42 x 52 43 x 63 51 x 63 53 x 73	No chg. No chg. No chg. No chg. No chg. No chg.	61" 67" 69" 80" 80"	400 lbs. 450 lbs. 500 lbs. 550 lbs. 600 lbs. 750 lbs.



### **MODEL DMS**

Loads Glass down-blanket up.  $360^{\circ}$  Rotor Plate allows operator to print from overhead or *either* vertical position (1) away from operator (2) toward operator.

## **PRICE INCLUDES:**

- (1) Special DOUTHITT "DEEP DRAW" BLACK Blanket. Under vacuum, this blanket swiftly molds itself to the shape of the silk screen frame and holds your positive in perfect contact.
- (2) Heavy Duty Vacuum Pump and Motor.
- (3) Vacuum Relief Bleeder Valve and vacuum gauge.
- (4) Optic clear A-1 Select Glass.
- (5) Special Rotor Locking Mechanism permits easy-sure stops for horizontal and vertical positions.
- (6) Positive locking device for perfect vacuum.
- (7) On sizes 37 x 47, 42 x 52 and 43 x 63, Rotating and locking is actuated by convenient Foot Treadle.

Size Inside Blanket Beading	Crating	Floor Space	Approx. Crated Weight
23 x 29	No chg.	30 x 37	228 lbs.
27 x 31	No chg.	33 x 39	255 lbs.
29 x 37	No chg.	35 x 45	273 lbs.
31 x 41	No chg.	35 x 49	303 lbs.
37 x 47	No chg.	40 x 54	335 lbs.
42 x 52	No chg.	45 x 59	375 lbs.
43 x 63	No chg.	46 x 71	450 lbs.
	e e	Manufa	ctured by: Ti



Electrical Specifications – 115 Volt, 60 Cycle, Single Phase, A.C.

Specify if 230 Volt, 60 Cycle, Single Phase, A.C. preferred – No extra charge.

Special Electrical requirements available on request.

Manufactured by: The Douthitt Corporation, 245 Adair St., Detroit, Michigan 48207 Toll Free 1-800-DOUTHIT(T) Phone 313-259-1565

Established 1919 · Fax No. 313-259-6806

www.douthittcorp.com · E-Mail: em@douthittcorp.com

